

Model **PECOLIFT** LOW-LEVEL ACCESS



We call it 'Non-Powered, Powered Access'

Battery and electric power free, the PecoLift is elevated by simply and easily rotating the handle; the patented lift mechanism glides you smoothly to your chosen working height in seconds.

With no batteries (to charge and look after) and no hydraulic oil the PecoLift is truly an Eco friendly solution. It's tiny footprint and simplicity of use finally provides a purely mechanical solution that doesn't involve erecting, unfolding or climbing.



Key Features

- Intuitive to operate - turn handle to elevate
- Patented* lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (985 x 700 mm)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

PATENTED*
STORED
POWER
SYSTEM

PUSH AROUND - Self Powered

Indoor Use

Working Height: 3.5 m

Applications: Pipe Work,
M&E. Cleaning. Painting.
Retail. FM.

Model PECOLIFT

LOW-LEVEL ACCESS

Specifications

WORKING DIMENSIONS

Maximum working height:	3.50 m
Maximum platform height:	1.50 m
Basket dimensions:	720 mm (L) x 600 mm (W)
Working footprint:	985 mm x 700 mm
Safe working load:	150 kg (1 person + tools)
Maximum manual force:	200N
Maximum gradient for operation:	0 degrees
Maximum wind force:	Internal use only, 0 (zero) mph
Maximum wheel force:	125 kg
Sound pressure level:	Less than 70 DbA

CLOSED DIMENSIONS

Length:	985 mm
Width:	700 mm
Height:	1.55 m
Weight:	180 kg

LIFT CYCLES Unlimited

Safety features

- Auto-braked on entering basket
- 'Auto-lok' brake on elevation
- Elevates only when operated
- Lifting mechanism interlocked



IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

JLG®

JLG EMEA BV

Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Phone: +31 (0)23 565 5665
www.jlg.com



An Oshkosh Corporation Company